

CompactCG Specifications

CompactCG All Systems Minimum System Specifications	CompactCG Analog Video I/O Standards Supported	CompactCG SD-SDI Video I/O Standards Supported
<p>CPU Intel Atom Core 2 Duo 1.6 GHz</p> <p>OS Windows XP Professional</p> <p>RAM 1GB</p> <p>Hard Drive 80GB SATA HDD (7200RPM)</p> <p>Optical Drive 20X DVD-RW</p> <p>Ports 1 Ethernet 1000 BaseT (RJ-45) 1 RS-232 (DB9) 1 PS2 Keyboard, Mouse 4 USB 2.0</p> <p>Power Specifications Power Supply: 220W 110/220 Volt 60/50 Hz (Auto-sense)</p> <p>Physical dimensions 1RU rack mount chassis Height: 1.75" (4.45cm) Width: 19 inches (48.26 cm) Depth: 15" (38.10 cm) Weight: 20lb (9.07 kg)</p>	<p>Analog SMPTE 170M NTSC 720x486 PAL 720x576</p> <p>Input Composite, YPbPr, Y/C fill</p> <p>Output Composite, YPbPr, Y/C fill Composite key System Genlock Reference Input (BB or CVBS) Internal, Input video</p>	<p>Analog SMPTE 170M NTSC 720x486 PAL 720x576</p> <p>SD-SDI SMPTE 259M (both 4:3 and 16:9 supported)</p> <p>Input Composite, YPbPr, Y/C, Passes VBI SD-SDI, Passes VBI</p> <p>Output Composite, YPbPr, Y/C fill Composite key SD-SDI key and fill System Genlock Reference Input (BB or CVBS) Internal, Input video</p>